



Electric Pedestrian Pallet Truck KH.HS 2000

Standard equipment

- **Heavy duty application**
- Max travel speed - **9,0km/h**
- Capacity - **2000 kg**
- Lifting height - **125 mm**
- **AC** drive motor - **2,5 kW**:
 - Maintenance free
 - External Encoder
 - Low noise level
- **DC** pump motor - **2,0 kW**
- Electronics - **modern CANBUS-architecture** requiring less wiring, giving better reliability, providing easy and fast diagnostics
- Speed control by **pulse controller AC/250A** including regenerative braking with energy reclamation to the battery
- Horn
- Automatic Braking:
 - Emergency and Parking electromagnetic brake
 - Regenerative braking when releasing accelerator in a neutral position or reversing the travel direction
- **Traction battery 24V 2PzS/250Ah, C5** / standard wet battery
- High frequency/**HF** automatic on-board **charger 24V/30A**
- EMERGENCY Switch
- Multifunction Digital Indicator displaying:
 - Battery's state of charge
 - Hour meter
 - Alarms
- Rollers and wheels - VULKOLLAN. Load side - Tandem rollers as standard
- Two castor wheels (left and right Driver side) and Spring loaded Drive Wheel in the middle
- **CREEP SPEED** function – travelling in restricted areas with Tiller-arm in upright position
- **Automatically foldable Driver`s platform**
- In accordance with **EN 1726-2** requirements:
 - Automatically foldable driver's platform (rubber cushioning for low-stress);
 - Manually foldable Sideguards (rubber cushioning for gentle keeping of Driver's body within the Truck's contour);
 - Automatic Travel speed reduction with the Platform or even only one of the two Safeguards in vertical position;
 - Automatic Travel speed reduction when cornering more than 10° left/right.
- Virtually maintenance-free Drive-wheel unit:
 - Modern AC traction motor in vertical position
 - High efficient gear box /gears in oil bath - no oil change required for life
 - High quality Traction wheel with Polyurethane, 93° Shore A tyre (other tyres available on request)
 - High quality Electromagnetic Brake with environment-friendly friction lining.

Optional equipment

- Batteries with higher capacity
- Authorized access with **PIN-Code management**
- Sideways battery removal in a multi-shift applications
- Hand trolley for sideways battery removal
- Gel/maintenance-free batteries HAWKER "Evolution"

Electric Stand-on Pallet Truck KH.HS 2000

Type sheet for industrial Trucks according to VDI 2198

		VENI			
Characteristics	1.1	Manufacturer			KH.HS 2000
	1.2	Manufacturer's type designation			Battery
	1.3	Power unit			Stand-on/Pedestrian
	1.4	Operation (pedestrian, stand on, seated)			
	1.5	Load capacity	Q	(kg)	2000
	1.6	Load centre	c	(mm)	600
	1.8	Axle centre to fork face	x	(mm)	862(*)
	1.9	Wheelbase	y	(mm)	1320(*)
	Weight	2.1	Service weight incl. battery		(kg)
Wheel/tyres	3.1	Tyres front/rear (Polyurethane/PU, Vulkollan/VU)			VU/VU
	3.2	Tyre size, front		(mm)	D 230x70
	3.3	Tyre size, rear		(mm)	D 85x70
	3.4	Support wheels		(mm)	D 150x50
	3.5	Wheels, number front / rear (x=driven)		(mm)	1x+2/4
	3.6	Track width, front	b ₁₀	(mm)	520
	3.7	Track width, rear	b ₁₁	(mm)	375
Dimensions	4.4	Lift	h ₃	(mm)	125
	4.9	Height of tiller in drive position min./max.	h ₁₄	(mm)	1200/1450
	4.15	Fork height, lowered	h ₁₃	(mm)	85
	4.19	Overall length with/without platform	l ₁	(mm)	2254/1861
	4.20	Length to fork face with/without platform	l ₂	(mm)	1104/711
	4.21	Overall width	b ₁	(mm)	740
	4.22	Fork dimensions	s/e/l	(mm)	55/185/1150
	4.25	Overall forks width	b ₅	(mm)	560
	4.32	Ground clearance, centre of wheelbase	m ₂	(mm)	30/155
	4.34	Aisle width with pallet 800x1200 mm along forks with/without platform	Ast	(mm)	2504/2111
4.35	Turning radius with/without platform	Wa	(mm)	1966/1573	
Performance	5.1	Travel speed, with/without load		(km/h)	8.5/9.0
	5.2	Lifting speed, with/without load		(m/s)	0.060/0.090
	5.3	Lowering speed, with/without load		(m/s)	0.065/0.050
	5.8	Maximum gradeability, with/without load		(%)	8/16
	5.10	Service brake			Electromagnetic
Drive	6.1	Drive motor, rating S2 60 min		(kW)	2.5
	6.2	Lift motor, rating S3 15%		(kW)	2.0
	6.4	Battery voltage/rated capacity C5		(V/Ah)	24/250
Others	8.1	Type of drive control			Pulse controller
					AC/250A

(*) - Load section lowered+72 mm

