



Electric Pedestrian Pallet Truck KH.LS 2000

Standard equipment

- **Heavy duty application**
- Max travel speed - **6,0km/h**
- Capacity - **2000 kg**
- Lifting height - **125 mm**
- **AC** drive motor - **1,3 kW**:
 - Maintenance free
 - External Encoder
 - Low noise level
- **DC** pump motor - **2,0 kW**
- Electronics - **modern CANBUS-architecture** requiring less wiring, giving better reliability, providing easy and fast diagnostics
- Speed control by **pulse controller AC/180A** including regenerative braking with energy reclamation to the battery
- Horn
- Automatic Braking:
 - Emergency and Parking electromagnetic brake
 - Regenerative braking when releasing accelerator in a neutral position or reversing the travel direction
- **Traction battery 24V 2PzS/250Ah, C5** / standard wet battery
- High frequency/**HF** automatic on-board **charger 24V/30A**
- EMERGENCY Switch
- Multifunction Digital Indicator displaying:
 - Battery's state of charge
 - Hour meter
 - Alarms
- Rollers and wheels - Polyurethane. Load side - Tandem rollers as standard
- Two castor wheels (left and right Driver side) and Spring loaded Drive Wheel in the middle
- **CREEP SPEED** function - travelling in restricted areas with Tiller-arm in upright position
- Virtually maintenance-free Drive-wheel unit:
 - Modern AC traction motor in vertical position
 - High efficient gear box /gears in oil bath - no oil change required for life
 - High quality Traction wheel with Polyurethane, 93° Shore A tyre (other tyres available on request)
 - High quality Electromagnetic Brake with environment-friendly friction lining.

Optional equipment

- Batteries with higher capacity
- Automatically foldable Driver's platform
- Authorized access with **PIN-Code management**
- Performance package (incl. **AC drive motor - 1,5 kW** and **pulse controller AC/250A**)
- Gel/maintenance-free batteries HAWKER "Evolution"

Electric Pedestrian Pallet Truck KH.LS 2000

Type sheet for industrial Trucks according to VDI 2198

Characteristics	1.1	Manufacturer			VENI
	1.2	Manufacturer's type designation			KH.LS 2000
	1.3	Power unit			Battery
	1.4	Operation			Pedestrian
	1.5	Load capacity	Q	(kg)	2000
	1.6	Load centre	c	(mm)	600
	1.8	Axle centre to fork face	x	(mm)	862(*)
	1.9	Wheelbase	y	(mm)	1320(*)
	Weight	2.1	Service weight incl. battery		(kg)
Wheel/tyres	3.1	Tyres front/rear (Polyurethane/PU, Vulkollan/VU)			PU/PU
	3.2	Tyre size, front		(mm)	D 230x70
	3.3	Tyre size, rear		(mm)	D 85x70
	3.4	Support wheels		(mm)	D 150x50
	3.5	Wheels, number front / rear (x=driven)		(mm)	1x+2/4
	3.6	Track width, front	b ₁₀	(mm)	520
	3.7	Track width, rear	b ₁₁	(mm)	375
Dimensions	4.4	Lift	h ₃	(mm)	125
	4.9	Height of tiller in drive position min./max.	h ₁₄	(mm)	1040/1330
	4.15	Fork height, lowered	h ₁₃	(mm)	85
	4.19	Overall length	l ₁	(mm)	1810
	4.20	Length to fork face	l ₂	(mm)	660
	4.21	Overall width	b ₁	(mm)	736
	4.22	Fork dimensions	s/e/l	(mm)	55/165/1150
	4.25	Overall forks width	b ₅	(mm)	540
	4.32	Ground clearance, centre of wheelbase	m ₂	(mm)	30/155
	4.34	Aisle width with pallet 800x1200 mm along forks	Ast	(mm)	2068
4.35	Turning radius	Wa	(mm)	1530	
Performance	5.1	Travel speed, with/without load		(km/h)	5.4/6.0
	5.2	Lifting speed, with/without load		(m/s)	0.060/0.090
	5.3	Lowering speed, with/without load		(m/s)	0.065/0.050
	5.8	Maximum gradeability, with/without load		(%)	8/16
	5.10	Service brake			Electromagnetic
Drive	6.1	Drive motor, rating S2 60 min		(kW)	1.3
	6.2	Lift motor, rating S3 15%		(kW)	2.0
	6.4	Battery voltage/rated capacity C5		(V/Ah)	24/250
Others	8.1	Type of drive control			Pulse controller
					AC/180A

(*) - Load section lowered +72 mm

KH.LS 2000

