



## Electric Pedestrian Pallet Truck KH.LS 3000

### Standard equipment

- **Heavy duty application**
- Max travel speed - **6,0km/h**
- Capacity - **3000 kg**
- Lifting height - **125 mm**
- **AC** drive motor - **1,3 kW**:
  - Maintenance free
  - External Encoder
  - Low noise level
- **DC** pump motor - **2,0 kW**
- Electronics - **modern CANBUS-architecture** requiring less wiring, giving better reliability, providing easy and fast diagnostics
- Speed control by **pulse controller AC/180A** including regenerative braking with energy reclamation to the battery
- Horn
- Automatic Braking:
  - Emergency and Parking electromagnetic brake
  - Regenerative braking when releasing accelerator in a neutral position or reversing the travel direction
- **Traction battery 24V 2PzS/250Ah, C5** / standard wet battery
- High frequency/**HF** automatic on-board **charger 24V/30A**
- EMERGENCY Switch
- Multifunction Digital Indicator displaying:
  - Battery's state of charge
  - Hour meter
  - Alarms
- Rollers and wheels - Polyurethane. Load side - Tandem rollers as standard
- Two castor wheels (left and right Driver side) and Spring loaded Drive Wheel in the middle
- **CREEP SPEED** function - travelling in restricted areas with Tiller-arm in upright position
- Virtually maintenance-free Drive-wheel unit:
  - Modern AC traction motor in vertical position
  - High efficient gear box /gears in oil bath - no oil change required for life
  - High quality Traction wheel with Polyurethane, 93° Shore A tyre (other tyres available on request)
  - High quality Electromagnetic Brake with environment-friendly friction lining.

### Optional equipment

- Batteries with higher capacity
- Automatically foldable Driver's platform
- Authorized access with **PIN-Code management**
- Performance package (incl. **AC drive motor - 1,5 kW** and **pulse controller AC/250A**)
- Gel/maintenance-free batteries HAWKER "Evolution"

## Electric Pedestrian Pallet Truck KH.LS 3000

### Type sheet for industrial Trucks according to VDI 2198

Characteristics	1.1	Manufacturer			<b>VENI</b>
	1.2	Manufacturer's type designation			<b>KH.LS 3000</b>
	1.3	Power unit			Battery
	1.4	Operation			Pedestrian
	1.5	Load capacity	Q	(kg)	<b>3000</b>
	1.6	Load centre	c	(mm)	600
	1.8	Axle centre to fork face	x	(mm)	862(*)
	1.9	Wheelbase	y	(mm)	1320(*)
	Weight	2.1	Service weight incl. battery		(kg)
Wheel/tyres	3.1	Tyres front/rear (Polyurethane/PU, Vulkollan/VU)			PU/PU
	3.2	Tyre size, front		(mm)	D 230x70
	3.3	Tyre size, rear		(mm)	D 85x80
	3.4	Support wheels		(mm)	D 150x60
	3.5	Wheels, number front / rear (x=driven)		(mm)	1x+2/4
	3.6	Track width, front	b <sub>10</sub>	(mm)	520
	3.7	Track width, rear	b <sub>11</sub>	(mm)	375
Dimensions	4.4	Lift	h <sub>3</sub>	(mm)	125
	4.9	Height of tiller in drive position min./max.	h <sub>14</sub>	(mm)	1040/1330
	4.15	Fork height, lowered	h <sub>13</sub>	(mm)	85
	4.19	Overall length	l <sub>1</sub>	(mm)	1810
	4.20	Length to fork face	l <sub>2</sub>	(mm)	660
	4.21	Overall width	b <sub>1</sub>	(mm)	736
	4.22	Fork dimensions	s/e/l	(mm)	55/185/1150
	4.25	Overall forks width	b <sub>5</sub>	(mm)	560
	4.32	Ground clearance, centre of wheelbase	m <sub>2</sub>	(mm)	30/155
	4.34	Aisle width with pallet 800x1200 mm along forks	Ast	(mm)	2068
4.35	Turning radius	Wa	(mm)	1530	
Performance	5.1	Travel speed, with/without load		(km/h)	5.2/6.0
	5.2	Lifting speed, with/without load		(m/s)	0.060/0.090
	5.3	Lowering speed, with/without load		(m/s)	0.065/0.050
	5.8	Maximum gradeability, with/without load		(%)	8/16
	5.10	Service brake			Electromagnetic
Drive	6.1	Drive motor, rating S2 60 min		(kW)	1.5
	6.2	Lift motor, rating S3 15%		(kW)	2.0
	6.4	Battery voltage/rated capacity C5		(V/Ah)	24/250
Others	8.1	Type of drive control			Pulse controller
					AC/180A

(\*) - Load section lowered +72 mm

## KH.LS 3000

