



Electric Pedestrian Pallet Stacker KMS.AC 1250/3,0

Standard equipment

- Heavy-duty application
- Max travel speed 6,0km/h
- Capacity – **1250 kg**
- Lifting height – **3.0 m**
- **AC** drive motor - **1,3 kW**:
 - Maintenance free
 - External Encoder
 - Low noise level
- **DC** pump motor – **2,0 kW**
- **Electronics - modern CANBUS-architecture** requiring less wiring, giving better reliability, providing easy and fast diagnostics
- Speed control by pulse controller **COMBI AC/250A** including regenerative braking with energy reclamation to the battery
- Horn
- Automatic Braking:
 - Emergency and Parking electromagnetic brake
 - Regenerative braking when releasing Accelerator in a neutral position or reversing the travel direction
- **Traction battery 24V 2PzS/160Ah C5** / standard wet **Pb Acid** battery
- **High frequency/HF** automatic on-board charger **24V/30A**
- EMERGENCY Switch
- Multifunction Digital Indicator displaying:
 - Battery's state of charge
 - Hour meter
 - Alarms
- **Proportional hydraulics** for smooth, step-less Lifting/Lowering speed control
- Rollers and wheels - Polyurethane. Load side - Tandem rollers as standard
- Two castor wheels (left and right Driver side) and Spring loaded Drive Wheel in the middle
- **CREEP SPEED** function – travelling in restricted areas with Tiller-arm in upright position
- Automatic Travel speed reduction when forks raised 1200mm and more
- Robust Two stage mast with central cylinder
- The Low centre of gravity-Chassis, strong masts and wheel layout concept – leading to high Residual capacity
- Virtually maintenance-free Drive-wheel unit:
 - Modern AC traction motor in vertical position
 - High efficient gear box /gears in oil bath - no oil change required for life
 - High quality Traction wheel with Polyurethane, 93° Shore A tyre (other tyres available on request)
 - High quality Electromagnetic Brake with environment-friendly friction lining.

Optional equipment

- Batteries with higher capacity
- Foldable driver's platform
- Authorized access with **PIN-Code management**
- Straddle legs version, including Forks 40/100/1200mm ISO/FEM Class 2B
- Sideways battery removal in a multi-shift applications
- Gel/maintenance-free batteries HAWKER "Evolution"
- Initial lift
- Choice of mast:
 - Different Lifting heights
 - Clear view mast
 - Full free lift mast
- **FLEET management unit**

Electric Pedestrian Pallet Stacker KMS.AC 1250/3,0

Type sheet for industrial Trucks according to VDI 2198

		VENI				
Characteristics	1.1	Manufacturer		KMS.AC 1250/3,0		
	1.2	Manufacturer's type designation		Battery		
	1.3	Power unit		Pedestrian		
	1.4	Operation				
	1.5	Load capacity	Q	(kg)	1250	
	1.51	Residual capacity	Qres	-	-	
				$h_3+h_{13} = 2300$ mm	(kg)	1250
				$h_3+h_{13} = 3000$ mm	(kg)	800
	1.6	Load centre	c	(mm)	600	
	1.8	Axle centre to fork face	x	(mm)	690	
1.9	Wheelbase	y	(mm)	1239		
Weight	2.1	Service weight incl. battery	(kg)	830		
Wheels/tyres	3.1	Tyres front/rear (Polyurethane/PU, Vulkollan/VU)		PU/PU		
	3.2	Tyre size, front	(mm)	D 230x70		
	3.3	Tyre size, rear	(mm)	D 85x70		
	3.4	Support wheels	(mm)	D 150x50		
	3.5	Wheels, number front / rear (x=driven)	(mm)	1x+2/4		
	3.6	Track width, front	b₁₀	(mm)	720	
	3.7	Track width, rear	b₁₁	(mm)	410	
Dimensions	4.2	Height, mast lowered	h₁	(mm)	2060	
	4.3	Free lift	h₂	(mm)	120	
	4.4	Lift	h₃	(mm)	2910	
	4.5	Height, mast extended	h₄	(mm)	3455	
	4.9	Height of tiller in drive position min./max.	h₁₄	(mm)	1200/1310	
	4.15	Fork height, lowered	h₁₃	(mm)	90	
	4.151	Fork height, lifted	h₃+h₁₃	(mm)	3000	
	4.19	Overall length	l₁	(mm)	1888	
	4.20	Length to fork face	l₂	(mm)	738	
	4.21	Overall width	b₁	(mm)	862	
	4.22	Fork dimensions	s/e/l	(mm)	55/165/1150	
	4.25	Overall forks width	b₅	(mm)	570	
	4.32	Ground clearance, centre of wheelbase	m₂	(mm)	35	
	4.34	Aisle width with pallet 800x1200 mm along forks	Ast	(mm)	2276	
4.35	Turning radius	Wa	(mm)	1428		
Performance	5.1	Travel speed, with/ without load	(km/h)	5.5/6.0		
	5.2	Lifting speed, with/ without load	(m/s)	0.136/0.160		
	5.3	Lowering speed, with/ without load	(m/s)	0.190/0.160		
			(m/s)	0.095/0.080		
	5.8	Maximum gradeability, with/ without load	(%)	8/15		
5.10	Service brake		Electromagnetic			
Drive	6.1	Drive motor, rating S2 60 min	(kW)	1.3		
	6.2	Lift motor rating S3 15%	(kW)	2.0		
	6.4	Battery voltage/ rated capacity C5	(V/Ah)	24/160		
Others	8.1	Type of drive control		Pulse controller COMBI AC/250A		

